

S750TST6

75 cm, FRIDGE AND FREEZER, OT Model

BUILT-IN

INTEGRATED® SERIES



Fhiaba



FEATURES

- Made in Italy: Designed and built entirely in Italy with artisanal precision
- Long Term Reliability: Premium materials and rigorous testing ensure consistent, durable performance
- Galvanized Steel Structure: Strength and stability engineered to last
- Antibacterial Interior: Hygienic surfaces preserving freshness and bottle quality
- EventLift™: Shelves adjustable to any height without removal
- ProVent™: Uniform cold air distribution across every zone
- EquiLance™: Patented variable pivot hinge for silent, stable movement
- OptiView™: Diffuse, uniform LED lighting
- Full Color TFT Display: Clear, intuitive, high definition interface
- 100% Total No Frost: Automatic system that prevents ice formation and ensures impeccable humidity control
- Variable Speed Compressors: Precise temperature control and reduced vibrations
- Sabbath Mode: Dedicated function for observance needs
- Easy Installation: Adjustable feet and rear wheels
- Low Temperature Zone: Dedicated area with a temperature 2°C lower than the refrigerator compartment, ideal for meat, fish, and vegetables
- Tempered Glass Shelves: With aluminum profiles
- TriMode™ Lower drawer configurable as refrigerator, fresh zone, or freezer

GENERAL PROPERTIES

Equilance Hinge	YES
Soft-Closing Glides	YES
Low Vibration	YES
OptiView (Led Light Spots)	YES
Shelves	4 - 1 fixed 3 adjustable
Type Of Shelves	Glass
Door Bins	3
Fridge Interior Drawers	2
Freezer Drawers	1
Evenlift Shelves	YES
Full Extension Shelves 90° Door Opening	NO
Full Extension Drawers 90° Door Opening	YES
Defrost Process	AUTOMATIC
Ice Maker With Water Filter	NO
Door Open Alarms	YES
Shopping Fridge	YES
Shopping Freezer	YES
Power Failure Alert	YES
Water Dispenser With Water Filter	NO



S750TST6

75 cm, FRIDGE AND FREEZER, OT Model

BUILT-IN

INTEGRATED® SERIES

PRODUCT DETAIL



1D | 1BD | 2M

D = door

BD = drawer

M = separate microclimates

CAPACITY		DIMENSIONS & WEIGHT	
Volume Compartment 1 (L)	335	Height of the product (closed weels)(mm)	2120
Volume Compartment 2 (L)	N/A	Adjustable feet height (mm)	25
Volume Compartment 3 (L)	105	Width of the product (mm)	749
Total Net Volume (L)	440	Depth of Product without handle (mm)	610
Total Gross Volume (L)	461	Wall cavity height (mm)	2134
Compartment 1 / Upper wine cellar capacity (bottles)	N/A	Wall cavity width (mm)	750
Compartment 2 / Lower wine cellar capacity (bottles)	N/A	Wall cavity depth (mm)	650
Compartment 3 / Bottom wine cellar capacity (bottles)	N/A	Net Weight (kg)	169
		Gross Weight (kg)	190
TECHNICAL DETAILS		TEMPERATURE RANGES	
Total absorbed current (A)	2	Climatic compartments	2
Voltage (V)	220-240V	Compartment 1 / Upper temperature (°C)	from 2 to 8
Frequency (Hz)	50/60 Hz	Compartment 2 / Middle temperature (°C)	from N/A to N/A
Power Cord Length (mm)	2	Low temp zone	YES
Plug Type	Tipo F (Schuko) 16A IEC13 10A	Compartment 3 / Low temperature (°C)	from -15 to -22
Climatic class	SN/T	Dual zone	NO
Noise level (dB)	41	ACCESSORIES	
Refrigerant (gas)	R600a	• Stainless steel sides panels • Joining kit • Stainless steel tubular handles Ø30mm • Stainless steel tubular handles Ø18mm • Stainless steel panels • Stainless steel portal for freestanding • Extra length anti-tipping kit • Anti-condensation kit • Cleaning kit • FLD - Fhiaba Link Device • Front ventilation kit • 90° Door stop	
Water connection / female attachment	/		
EFFICIENCY			
New Energy Label class	E		
Energy consumption (kWh/year)	271		

S750TST6


75 cm, FRIDGE AND FREEZER, OT Model

BUILT-IN

INTEGRATED® SERIES


PRODUCT SPECIFICATIONS AND DIMENSIONS

Fhiaba




FRONT VIEW

SIDE VIEW




TECHNICAL DATA	
Niche Width A (mm)	750
Unit Width B (mm)	737
Unit Width with lateral frames C (mm)	749


TOP VIEW,
HINGE 105°



TOP VIEW,
HINGE 90°



PLINTH SIZE



i For installation specifications, please consult with Fhiaba. For optimum installation, we recommend using the actual product as the best guide.

i Based on the adjustment of the feet and the height of the panel from the floor, the customer defines the perforated plinth to be installed on the equipment.


S750TST6

75 cm, FRIDGE AND FREEZER, OT Model

BUILT-IN

INTEGRATED® SERIES

CUSTOM PANELS INFORMATION



INTEGRATED PANEL RECOMMENDATIONS

Panels with thickness ranging between 18 mm and 28 mm

Door Panels Weight Max	23 kg
Drawer Panels Weight Max	11 kg



For installation specifications, please consult with Fhiaba.
For optimum installation, we recommend using the actual product as the best guide.

S750TST6



75 cm, FRIDGE AND FREEZER, OT Model

BUILT-IN

INTEGRATED® SERIES

PRODUCT SPECIFICATIONS AND DIMENSIONS

Electrical Connection



Electrical and water connections (if applicable) should be reachable without having to uninstall the appliance. If the connections must be made directly behind the appliance then it is recommended to recess those connections.

IMPORTANT: do not put the water shut-off valve behind the appliance where it will be inaccessible.



For installation specifications, please consult with Fhiaba. For optimum installation, we recommend using the actual product as the best guide.